

线条灯-HY3

LED Linear Light -HY3



LLS-HY3

产品特点 Features

- * 光源采用低热阻，高光效的品牌灯珠，极高的光效率，达到2万小时的寿命
- * 灯体采用航空级铝材，具有较好的散热性能
- * 控制芯片采用，成熟稳定的方案，确保批量的稳定性
- * PC罩具有高透光性及显色效果
- * Low thermal resistance, high efficiency LEDs used, low light decay rate extends LEDs life span to 30,000 hrs
- * The lamp body adopts aviation aluminum, has good heat dissipation performance
- * Control chip, mature and stable solution, to ensure the stability of the batch
- * PC cover high cast light and the effect of mixed color

选配型号 & 技术参数 Model Info & Specifications

型号/Model	LLS-HY3-2X	LLS-HY3-4X
尺寸 /Size	1100mm*30*80mm	1100mm*30*80mm
材质 /Material	乳白PC罩+铝合金/White PC cover+Al alloy	乳白PC罩+铝合金/White PC cover+Al alloy
重量 /Weight	0.7kg±5%	1.3kg±5%
灯珠数 /LED Quantity	24pcs SMD5050(3x1)	48pcs SMD5050(3x1)
灯珠颜色 /Color	白光全彩或单色 /RGB or Steady Color	白光全彩或单色 /RGB or Steady Color
输入电压 /Input Volt	24VDC	24VDC
最大功率 /Power(Max.)	6W	12W
控制方式 /Control Mode	常亮或调光 /Steady or Dimmable	常亮或调光 /Steady or Dimmable


物理 & 安装尺寸 Physical & Installation Dimensions



安装尺寸/Installation Dimensions


LLS-MY3
单位/Unit : mm

照度图 Illuminance At A Distance



Note: The Curves indicate the illuminated area and the average illumination when the luminance is at different distance.

光强分布曲线 Distribution Curve



LLS-MY3 Beam Angle: 120°

CE IP65
EPISTAR CREE